

MICHELIN® XZY® TIRE



All-position tube-type radial for
on/off road service.



MICHELIN® XZY® TIRE



ON/OFF ROAD APPLICATIONS

All-position tube-type radial for on/off road service.

Offset, block shoulder design promotes soft soil mobility.

Zigzag groove angles help resist stone retention and drilling.

Application specific compound to help resist aggressions from cutting and chipping.



Size	Load Range	Catalog Number	Tread Depth	Max. Speed (+)	Loaded Radius		Overall Diameter		Overall Width (‡)		Approved Wheel	Min. Dual Spacing (‡)		Revs Per Mile	Max. Load and Pressure Single				Max. Load and Pressure Dual			
			32nds	mph	in.	mm	in.	mm	in.	mm		in	mm		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
12.00R24 (1)	H	29163	23	65	22.4	568	48.1	1222	12.3	313	8.50	14.1	358	431	8820	110	4000	760	8050	110	3650	760

(1) Tube: 24Q - MSPN 11708; Flap: 24/25x8.50 E - MSPN 63382.
(*) Exceeding the lawful speed limit is neither recommended nor endorsed.
(‡) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.
MICHELIN® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations. Please consult wheel manufacturer's load and inflation limits. Never exceed wheel manufacturer's limits without permission of component manufacturer.

www.michelintruck.com

United States
Michelin North America, Inc.
One Parkway South
Greenville, SC 29615
1-888-622-2306

Canada
Michelin North America (Canada), Inc.
2500 Daniel Johnson, Suite 500
Laval, Quebec H7T 2P6
1-888-871-4444

Mexico
Industrias Michelin, S.A. de C.V.
Av. 5 de febrero No. 2113-A
Fracc. Industrial Benito Juarez
7 6120, Querétaro, Qro. Mexico
011 52 442 296 1600