



PORTABLE GENERATORS

When a power outage occurs, when a disaster strikes, when you need power at a remote location, a portable generator guarantees you a source of electricity.

Portable generators are gas-powered machines that provide you with the power you need anywhere you are. Power outlets on the unit allow you to plug in extension cords, electric-powered tools, and appliances.

While many people buy a generator in the event of a power outage at their home or business, a portable generator allows you to bring power where none is available.

Generators have a range of capabilities based on starting watts and running watts.

Running watts refers to the continuous power a generator can supply, and starting watts refers to the momentary boost of power the generator can supply to start a motor.



OVERVIEW

SUA15000EC

PORTABLE GENERATOR

- 15,000 Starting Watts
- 12,000 Running Watts

Commercial

- 680cc / 24hp OHV Twin Cylinder Engine
- Electric Start
- Runs for 7 Hours at 50% Load
- Sine Wave Technology
- EPA/CARB 50 States
- Pure sine wave, heavy-duty generator with electric start provides backup power for commercial businesses and home.



Model	SUA15000EC
UPC Code	851217006138
Running Watts	12,000
Starting Watts	15,000
Alternator	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Phase/ Frequency	Single/60Hz
Engine (OHV)	680cc/24hp
Starting Method	Electric Start
THD (Total Harmonic Distortion)	Less than 5%
Lubrication	Splash
Low Oil Shutdown	Automatic
Running VAC Amperage	50A
Multi Meter	Hour, Hz, Voltage
Direct Circuit (DC)	Yes
Low Oil Alert Lamp	Yes
Circuit Breaker	8.3A, 20A, 30A, 50A
120V 20A NEMA 5-20R Outlet	2 GFCI
120V 30A NEMA L5-30R Outlet	1
120/240V 30A NEMA L14-30R Outlet	1
120/240 V 50A NEMA L14-50R Outlet	1
Weather Protected Outlet Cover	4
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	8 gal. (30 L)
Run Time @ 50% Load	7 hours
Run Time @ 100% Load	5 hours
Engine Oil Capacity (Qt. / L)	1.16 qt. (1.1 L)
Built-in Gauge on Fuel Tank	Yes
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrester	Yes
Noise Level, dBA at 23 ft. (7m)	85
Durable Tubular Steel Frame	1.25 in diameter (32 mm)
Maintenance Free Battery	12V/36AH
Engine Oil Supplied	1.5 qt. 10W-30
DC Charging Cable	1
Spark Plug Socket	Yes
Wheel Kits	4-inch, 4-way
Gross Weight	447 lbs./196 kgs
Net Weight	392 lbs./171 kgs
Assembly Dimension	38.7 x 26.8 x 34.9 in.
Packing Dimension	40.2 x 27.2 x 37.8 in.
Warranty	
Emission Certification	EPA/CARB